RAY-MOTION
dedicated to motion
www.ray-motion.com

LIQUID TEMPERING SPECIFICATIONS 液温控制规格

Specifications 规格			
Liquid[(1)]	液体介质	Clean tap water with additive	含添加剂的洁净水
Temperature(°C)	温度		22-28
Flow rate(L/min)	流量		2-4
Liquid Pressure(bar)	液体压力		2-3

(1) Caution:
When using cooling water including deionised water, suitable additives must be used to prevent the growth of algae and protect the aluminium parts against corrosion.
Additive recommendations:Standard industrial applications: e.g. CCL(NALCO).
Please consult your additive supplier for dosage information.

(1) 注意：
当使用冷却水（含去离子水）时，必须添加适当的添加剂，以防藻类滋生，并保护铝制部件免受腐蚀。
添加剂推荐：标准工业应用如纳尔科闭式循环液。请咨询您的添加剂供应商以获取剂量信息。

AIR FLUSHING SPECIFICATIONS 气体吹扫规格

Specifications 规格			
Air	气体介质	Clean air free of water & oil ISO 8573.1:2001 Class 1.6.7	无油无水的洁净空气
Flow rate(L/min)	流量		20
Air Pressure(bar)	空气压力		0.5-1

The above information is subject to change withou notice.
上述信息如有变更，恕不另行通知。
2026