CAISUN

www.caisun.com

彩 信 与 您 共 精 彩

上海彩信电子有限公司
SHANGHAI CAISUN ELECTRONIC CO.,LTD

中美合作

上海彩信电子科技有限公司
SHANGHAI CAISUN ELECTRONIC TECHNOLOGY CO.,LTD



Quality and Peace of Mind

简 介

上海彩信电子科技有限公司是衡器仪表行业内的高科技企业。公司是由上海彩信电子有限公司和美方股东共同投资组建成立的外资企业。公司以研发、生产各种称重仪表及衡器配件为主导，并承接设计、定制各类非标准特殊的衡器仪表及称重系统，引进了最新的测力仪表技术。

公司的技术根基扎实，熟知行业特点，有多年的技术底蕴，产品功能强、质量好，性价比高，为业内人士所认同，集多方优势为一体，秉承“热忱为同行配套服务”的宗旨，提供全方位的优质服务。公司拥有自主的产品品牌，自行开发的产品拥有知识产权。

在与美方合作成立合资公司后，在引进资金的同时，也引进了国外先进的管理理念。同时外方负责引进新的技术项目，并向国际市场拓展、推荐。

Shanghai Caisun Electronic Technology Co.,Ltd. is a high-tech enterprise specializing in research and development, manufacturing and marketing of weighing indicators and accessories.The weighing indicators are designed for any weighing application and provide a range of configurations and functionality. They can be paired with a range of weighing scales and software for acomplete weighing solution.







XK315A1-1x Series OIML Approved Indicators

* Applications: electronic platform scale and weighing scale, etc.



XK315A1-10
Plastic Housing
6-digit 25.4mm LCD



XK315A1-11
304 Stainless Steel Housing
6-digit 25.4mm LCD



XK315A1-12
304 Stainless Steel Housing
6-digit 25.4mm LCD



XK315A1-13
Plastic Housing
6-digit 25.4mm LCD



10 V/m immunity to
radiated electromagnetic fields
Drive up to 4×350Ω or 8×700Ω load cell
20 hours of full charge battery operation
1,000,000 internal ADC counts
Quick recalibration due to change of environment
RS-232 / RS-485 interface with continuous data
output or command protocol
RS-232 serial printer interface
HI/OK/LO set-point
Low battery warning


Test certificate


Evaluation report


EU-type examination certificate


Test certificate

XK315A1-2x Series OIML Approved Indicators

* Applications: electronic platform scale and weighing scale, etc.



XK315A1-22
304 Stainless Steel Housing
6-digit 20.2mm Red LED



XK315A1-21
304 Stainless Steel Housing
6-digit 20.2mm Red LED



XK315A1-20
Plastic Housing
6-digit 20.2mm Red LED



XK315A1-23
Plastic Housing
6-digit 20.2mm Red LED



XK315A1-20G
Plastic Housing
6-digit 20.2mm Green LED



XK315A1-21G
304 Stainless Steel Housing
6-digit 20.2mm Green LED



XK315A1-22G
304 Stainless Steel Housing
6-digit 20.2mm Green LED



XK315A1-23G
Plastic Housing
6-digit 20.2mm Green LED



IP66

XK315A1-21F
304 Stainless Steel Housing
6-digit 20.2mm Red LED



IP66

XK315A1-21GF
304 Stainless Steel Housing
6-digit 20.2mm Green LED

NMi CERTIFIED OIML R76 OIML CE



10 V/m immunity to radiated electromagnetic fields
Drive up to 4×350Ω or 8×700Ω load cell
20 hours of full charge battery operation
1,000,000 internal ADC counts
RS-232 / RS-485 interface with continuous data output or command protocol
RS-232 serial printer interface
HI/OK/LO set-point / Low battery warning

ABS塑料外壳通用仪表 / ABS Plastic Housing Weighing Indicators

适用于电子台秤、地上衡等 Applications: electronic platform scale and weighing scale, etc.



XK315A1X
0.8英寸红色LED显示
6-digit 20.2mm Red LED



XK315A1G
0.8英寸绿色LED显示
6-digit 20.2mm Green LED



XK315C12
可选配两路独立串行输出
0.8英寸红色LED显示
Optional two independent RS-232 serial ports
6-digit 20.2mm Red LED



XK315A1-9
0.8英寸红色LED显示
6-digit 20.2mm Red LED



XK315A1-9G
0.8英寸绿色LED显示
6-digit 20.2mm Green LED



XK315A1-1
0.8英寸红色LED显示
6-digit 20.2mm Red LED

基本功能 Basic features:

电瓶充足可连续使用30小时以上
最多可接4只350Ω或8只700Ω传感器
kg - lb转换 / 动物秤功能
峰值保持功能 / 计数功能
RS-232 串行连续输出通讯接口 / RS-232打印输出
30 hours of full charge battery operation
Drive up to 4×350Ω or 8×700Ω load cell
Selectable kg and lb / Animal weighing function
Peak hold function / Counting function
RS-232 serial interface / Connect with printer

拓展功能 Expandable features:

可增配4G卡无线传输
可增配RS-485串行口
可增配蓝牙 / Wi-Fi无线通讯
可增配二 / 四点定值输出
可增配4-20mA模拟电流环输出
可增配机改电
Optional 4G transmission
Optional RS-485 serial interface
Optional bluetooth / Wi-Fi communication
Optional two / four set-point output function
Optional 4-20mA Analog output function
Optional mechanical scale function

大显示称重仪表 / Big Display Weighing Indicators

适用于电子台秤、地上衡等 Applications: electronic platform scale and weighing scale, etc.



XK315A1-7
304不锈钢外壳
1.5英寸红色LED显示
304 Stainless Steel Housing
6-digit 38.1mm Red LED

基本功能 Basic features:

电瓶充足可连续使用20 / 30小时以上
最多可接4只350Ω或8只700Ω传感器
kg - lb转换 / 动物秤功能 / 峰值保持功能 / 计数功能
RS-232串行连续输出通讯接口 / RS-232打印输出
20 / 30 hours of full charge battery operation
Drive up to 4×350Ω or 8×700Ω load cell
Selectable kg and lb / Animal weighing function
Peak hold function / Counting function
RS-232 serial interface / Connect with Printer



XK315A1-2L
304不锈钢外壳
七位1.4英寸液晶显示
304 Stainless Steel Housing
7-digit 35.6mm LCD

拓展功能 Expandable features:

可增配RS-485串行口
可增配蓝牙 / Wi-Fi无线通讯
可增配二 / 四点定值输出
可增配时钟功能
可增配机改电
Optional RS-485 serial interface
Optional bluetooth communication
Optional W-Fi communication
Optional two / four set-point output function
Optional date and time function
Optional mechanical scale function





XK315A1-2S
塑料外壳
1.5+0.8英寸双面红色LED显示
Plastic Housing
6-digit 38.1+20.2mm Double-side Red LED



XK315A1GB-5L
304不锈钢外壳
1英寸液晶显示
304 Stainless Steel Housing
6-digit 25.4mm LCD



XK315A1-2
塑料外壳
1.5英寸红色LED显示
Plastic Housing
6-digit 38.1mm Red LED



XK315A1GB-L
304不锈钢外壳
1英寸液晶显示
304 Stainless Steel Housing
6-digit 25.4mm LCD



XK315A1-9L
塑料外壳
1英寸液晶显示
Plastic Housing
6-digit 25.4mm LCD



XK315A1L
塑料外壳
1英寸液晶显示
Plastic Housing
6-digit 25.4mm LCD

304不锈钢称重仪表 / 304 Stainless Steel Housing Weighing Indicators

适用于电子台秤、地上衡等 Applications: electronic platform scale and weighing scale, etc.



XK315A1GB-3
0.8英寸绿色LED显示
6-digit 20.2mm Green LED



XK315A1RB-3
0.8英寸红色LED显示
6-digit 20.2mm Red LED



XK315A1GB-5
0.8英寸绿色LED显示
6-digit 20.2mm Green LED



XK315A1-8
0.56英寸红色LED显示
6-digit 14.2mm Red LED



XK315C12SS
可选配两路独立串行
0.8英寸红色LED显示
Optional two independent RS-232 serial ports
6-digit 20.2mm Red LED



XK315A1-2L
七位1.4英寸液晶显示
标配RS-485 Modbus-RTU接口
最多可增配3路独立串行输出
7-digit 35.6mm LCD
Standard RS-485 Modbus-RTU communication
Optional 3 ways isolation independent serial ports

基本功能 Basic features:

电瓶充足可连续使用20小时以上
最多可接4只350Ω或8只700Ω传感器
kg - lb转换 / 动物秤功能 / 峰值保持功能 / 计数功能
RS-232串行连续输出通讯接口 / RS-232打印输出
20 hours of full charge battery operation
Drive up to 4×350Ω or 8×700Ω load cell
Selectable kg and lb / Animal weighing function
Peak hold function / Counting function
RS-232 serial interface / Connect with printer

拓展功能 Expandable features:

可增配4G卡无线传输
可增配RS-485串行口
可增配蓝牙 / Wi-Fi无线通讯
可增配二 / 四点定值输出
可增配4-20mA模拟电流环输出
可增配机改电
Optional 4G transmission
Optional RS-485 serial interface
Optional bluetooth / Wi-Fi communication
Optional two / four set-point output function
Optional 4-20mA Analog output function
Optional mechanical scale function

上下限定值输出称重仪表 / HI-OK-LO Output Weighing Indicators

适用于电子台秤、地上衡等 Applications: electronic platform scale and weighing scale, etc.



XK315A1T
塑料外壳
0.8英寸高亮度红色LED显示
Plastic Housing
6-digit 20.2mm Red LED



XK315A1PC-T
塑料外壳
0.56英寸三排红色LED显示
Plastic Housing
17-digit 14.2mm Red LED



XK315A1GB-T
304不锈钢外壳
0.8英寸超高亮度绿色LED显示
304 Stainless Steel Housing
6-digit 20.2mm Green LED



XK315A1-2T
塑料外壳
1.5英寸红色LED显示
Plastic Housing
6-digit 38.1mm Red LED



XK315A1LT
塑料外壳
1英寸液晶显示
Plastic Housing
6-digit 25.4mm LCD



XK315A1-2LT
304不锈钢外壳
七位1.4英寸液晶显示
304 Stainless Steel Housing
7-digit 35.6mm LCD

基本功能 Basic features:

两点定值输出功能
最多可接4只350Ω或8只700Ω传感器
kg-lb转换
RS-232串行连续输出 / 打印输出
Two set-point output function
Drive up to 4×350Ω or 8×700Ω load cell
Selectable kg and lb / RS-232 serial interface
Connect with printer

拓展功能 Expandable features:

可增配RS-485串行口
可增配四点定值输出
可增配机改电
Optional RS-485 serial interface
Optional four set-point output function
Optional mechanical scale function

畜牧秤仪表 / Animal Fuction Indicators

适用于电子台秤、地上衡等 Applications: electronic platform scale and weighing scale, etc.



XK315A1X
0.8英寸数码管显示
6-digit 20.2mm LED



XK315C12
可选配两路独立串行输出
0.8英寸数码管显示
6-digit 20.2mm LED
2 way RS-232. it can connect remote display and PC



XK315A1GB-3
0.8英寸绿色LED显示
6-digit 20.2mm Green LED



XK315A1GB-5-LP-BQ
1英寸LCD显示
6-digit 25.4mm LCD



XK315C12SS-BQ
0.8英寸红色LED显示
带RS-232输出可接大屏幕
6-digit 20.2mm Red LED
RS-232 serial interface connect with display

电瓶充足可连续使用20 / 30小时以上
最多可接4只350Ω或8只700Ω 传感器
kg-lb转换 / 计数功能
RS-232串行连续或应答输出通讯接口
可增配RS-232 / RS-485串行口
20 / 30 hours of full charge battery operation
Drive up to 4x350Ω or 8x700Ω load cell
Selectable kg and lb / Counting function
RS-232 serial interface
Connect with printer
Optional RS-232 / RS-485 serial interface



无线称重仪表 / Wireless Weighing Indicators

适用于电子台秤、地上衡等 Applications: electronic platform scale and weighing scale, etc.

单秤台无线称重仪表 / Wireless weighing indicators for single platform



XK315A1W+CRW2
塑料外壳
Plastic Housing



XK315A1RB-WP+CRW2
304不锈钢外壳内置打印机
Built-In printer
304 Stainless Steel Housing



XK315A1RB-W+CRW2
304不锈钢外壳
304 Stainless Steel Housing

0.8英寸红色LED显示
秤台到仪表100米 / 500米无线传送数据
CRW2最多可接4只350Ω或8只700Ω传感器
kg - lb转换 / 动物秤功能 / 峰值保持功能 / 计数功能
RS-232串行连续输出通讯接口 / 打印输出功能
6-digit 20.2mm red LED
100m / 500m wireless connection with load cell
CRW2 can drive up 4X350Ω or 8X700Ω load cell
Selectable kg and lb / Animal weighing
Peak hold function / Counting function
RS-232 serial interface / Connect with printer

双秤台无线称重系列仪表 / Wireless weighing indicator for two platforms



XK315A1RB-WP+CRW2x2
304不锈钢外壳内置打印机
304 Stainless Steel Housing



XK315A1RB-W+CRW2x2
塑料外壳
Plastic Housing

0.8英寸红色LED显示
秤台到仪表100米 / 500米无线传送数据
每只CRW2最多可接4只350Ω或8只700Ω传感器
共可接8只350Ω或16只700Ω传感器
kg - lb转换 / 动物秤功能 / 峰值保持功能 / 计数功能
RS-232串行连续输出通讯接口 / 打印输出功能
6-digit 20.2mm red LED
100m / 500m wireless connection with load cell
Each CRW2 can drive up 4×350Ω or 8×700Ω load cell
Totally it can drive up 8×350Ω or 16×700Ω load cell
Selectable kg and lb / Animal weighing
Peak hold function / Counting function
RS-232 serial interface / Connect with printer



XK315A1RB-W+CRW2x2
304不锈钢外壳
304 Stainless Steel Housing

内置打印机称重仪表 / Built-In Printer Weighing Indicators

适用于电子台秤、地上衡等 Applications: electronic platform scale and weighing scale, etc.



XK315A1GB-5P-BQ
0.8英寸超高亮度绿色LED显示
6-digit 20.2mm Green LED



XK315A1GB-5-LP-BQ
1英寸LCD显示
6-digit 25.4mm LCD



XK315A1-7P-BQ
1.5英寸超大红色LED显示
6-digit 38mm Red LED



XK315A1-7P-ZS
1.5英寸超大红色LED显示
6-digit 38mm Red LED



XK315A1-2LP-BQ
七位1.4英寸超大液晶显示
标配RS-485 Modbus-RTU接口
7-digit 35.6mm LCD
Stardare RS-485 Modbus-RTU communication



XK315C12SS-BQ
0.8英寸超高亮度红色LED显示
带RS-232输出
6-digit 20.2mm Red LED
RS-232 serial interface

基本功能 Basic features:

304不锈钢外壳，内置打印机
自动识别热敏连续纸 / 热敏标签纸，换纸方便
44mm普通纸或58mm热敏连续纸 / 热敏标签纸
最多可接4只350Ω或8只700Ω传感器
kg - lb转换 / 动物秤功能 / 峰值保持功能 / 计数功能
304 Stainless Steel Housing with inside printer
44mm paper for ZS printer
58mm thermal / label paper for BQ printer
Easy to replace printer paper
Automatic recognition of thermal and label paper
Drive up to 4×350Ω or 8×700Ω load cell
Selectable kg and lb / Animal weighing function
Peak hold function / Counting function

拓展功能 Expandable features:

可增配机改电
可增配时钟功能
Optional mechanical scale function
Optional date and time function



Mechanical Scale Parts

IP66 防水仪表 / Water-Proof Weighing Indicators

适用于电子台秤、地上衡等 Applications: electronic platform scale and weighing scale, etc.



XK315A1GB-LF
1英寸LCD显示
LO / OK / HI三区域定值显示
6-digit 25.4mm LCD
HI/OK/LO set-point



XK315A1GB-F
0.8英寸超高亮度绿色LED显示
6-digit 20.2mm Green LED



XK315A1GB-5F
0.8英寸超高亮度绿色LED显示
6-digit 20.2mm Green LED

基本功能 Basic features:

304不锈钢外壳
电瓶充足可连续使用20小时以上
最多可接4只350Ω或8只700Ω传感器
kg - lb转换 / 动物秤功能 / 峰值保持功能 / 计数功能
304 stainless steel housing
20 hours of full charge battery operation
Drive up to 4×350Ω or 8×700Ω load cell
Selectable kg and lb / Animal weighing function
Peak hold function / Counting function

拓展功能 Expandable features:

可增配两点 / 四点 定值输出
可增配RS-232 / RS-485串行口
可增配时钟功能
Optional two / four set-porit output function
Optional RS-232 / RS-485 serial interface
Optional mechanical scale function



XK315A1GB-5-LF
1英寸LCD显示
LO / OK / HI三区域定值显示
6-digit 25.4mm LCD
HI/OK/LO set-point



XK315A1RB-5F
0.8英寸高亮度红色LED显示
6-digit 20.2mm Red LED



XK315A1-2F
塑料外壳
1.5英寸显示
Plastic Housing
6-digit 38.1mm red LED

其它防水产品 / Other Water-Proof Products

IP65

CX3S-F不锈钢防水大屏幕
CX3S-F Water-Proof Display



110V或220V AC供电
显示字高82mm
外形尺寸430*180*50cm
可连接60款以上知名称重仪表
AC 110V / 220V power supply
6-digit 82mm red LED
Dimensions 430 × 180 × 50cm
Connect with more than 60 models famous weighing indicators

YT系列塑料防水接线盒
YT series Junction Box



防水等级IP67 / 4-12线可选
德国胡默尔防水PG接头
美国伯恩斯电位器
调桥压或调信号两种模式可选
Ingress Protection Rating 67
4 / 6 / 8 / 10 / 12 line, totally 5 models
Hummel PG connecters
Bourns potentiometers
Available in bridge adjustment or precision trim pot modes

高性价比ABS塑料台秤小地磅通用仪表 / Weighing Indicators

适用于电子台秤、地上衡等 Applications: electronic platform scale and weighing scale, etc.



XK315A1-0
0.8英寸红色数码管显示
6-digit 20.2mm Red LED



XK315A1-0L
0.8英寸液晶显示
6-digit 20.2mm LCD



XK315A1-0X
0.8英寸红色数码管显示
6-digit 20.2mm Red LED

基本功能 Basic features:

电瓶充足可连续使用30小时以上
最多可接4只350Ω或8只700Ω传感器
kg - lb转换 / 峰值保持功能
RS-232串行连续输出通讯接口
RS-232打印输出
30 hours of full charge battery operation
Drive up to 4×350Ω or 8×700Ω load cell
Selectable kg and lb / Peak hold function
RS-232 serial interface / Connect with printer

拓展功能 Expandable features:

可增配RS-485串行口
可增配机改电
Optional RS-485 serial interface
Optional mechanical scale function



XK315J1
0.8英寸液晶显示
6-digit 20.2mm LCD

NEW

计数计价仪表 / Pricing–Counting Weihing Indicators

适用于电子台秤、地上衡等 Applications: electronic platform scale and weighing scale, etc.



XK315A1PC
塑料外壳
0.56英寸三排红色LED显示
Plastic Housing
17-digit 14.2mm Red LED



XK315A1PC-L
塑料外壳
超大LCD显示
Plastic Housing
17-digit large LCD



XK315A1GB-PCL
304不锈钢外壳
超大LCD显示
304 Stainless Steel Housing
17-digit large LCD



XK315A1GB-PC
304不锈钢外壳
0.56英寸三排红色LED显示
304 Stainless Steel Housing
17-digit 14.2mm Red LED

基本功能 Basic features:

电瓶充足可连续使用30小时以上
最多可接4只350Ω或8只700Ω传感器
kg - lb转换 / RS-232串行连续输出通讯接口
RS-232打印输出
Pricing-Counting weihing indicator
30 hours of full charge battery operation
Drive up to 4×350Ω or 8×700Ω load cell
Selectable kg and lb / RS-232 serial interface
Connect with printer

拓展功能 Expandable features:

可增配RS-485串行口
可增配机改电
可增配BMI体质指数功能
可增配文字输入
可增配两点定值输出
Optional RS-485 serial interface
Optional mechanical scale function
Optional BMI function
Optional letter input
OPtional two set-point output function

特殊功能仪表 / Special Functions Weighing Indicators

适用于电子台秤、地上衡等 Applications: electronic platform scale and weighing scale, etc.



XK315A1S
0.8英寸双面红色LED显示
塑料外壳
6-diglit 20.2mm Double-side Red LED
Plastic Housing



XK315A03
塑料外壳抗静电仪表
静电范围:接触6000V，环境8000V
Plastic Housing
Able to contact with 6000V static electricity directly and 8000V environmental static electricity



XK315A07
0.8英寸七位红色LED显示
塑料外壳
7-diglit 20.2mm Red LED
Plastic Housing



XK315A1-2S
1.5+0.8英寸双面红色LED显示
塑料外壳
6-digit 38.1+20.2mm Double-side Red LED
Plastic Housing

基本功能 Basic features:

电瓶充足可连续使用30小时以上
最多可接4只350Ω或8只700Ω传感器
kg - lb转换 / 动物秤功能
峰值保持功能 / 计数功能
RS-232串行连续输出 / RS-232打印输出
30 hours of full charge battery operation
Drive up to 4×350Ω or 8×700Ω load cell
Selectable kg and lb / Animal weighing function
Peak hold function / Counting function
RS-232 serial interface / Connect with Printer

拓展功能 Expandable features:

可增配RS-485串行口
可增配机改电
Optional RS-485 serial interface
Optional mechanical scale function





XK315A1-2L
304不锈钢外壳
1.4英寸液晶显示
304 Stainless Steel Housing
6-digit 35.6mm LCD

100-240V AC供电 / 内置电池
传感器输入信号范围±10mV
RS-485 Modbus-RTU应答方式或连续方式
动物秤功能 / 峰值保持功能
计数功能 / 双向称重功能
公斤-磅、克-盎司、无计量单位
减法秤功能
Input signal range:±10mV
Standard RS-485 Modbus-RTU communication
kg-lb.g-oz, or no weighing unit display
Animal weighing / Hold function
Counting function
Double-way weighing / Subtraction weighing

最多可增配3路RS-232 / RS-485通讯接口
可选Modbus-TCP网络通讯接口
可增配4-20mA模拟量输出接口
可增配上、下限报警输出 / 三色灯报警输出
Optional 3 ways isolated independent RS-232 / RS-485
Optional Modbus-TCP Network communication interface
Optional 4-20mA Analog current output function
Optional two / four set-point output function



XK315A1D
传感器测试仪
塑料外壳
Load cell tester
Plastic Housing

检测模拟传感器的零点 / 稳定性 / 线性
Load cell tester
Easy installation and wiring
Test the zero point of analog sensors
Test the stability of analog sensors

无缝对接绝大多数模拟传感器
Match with mostly load cell

控制系列仪表 / Weighing Controller

 **XK315A2-3** 塑料外壳 Plastic Housing	重量变送器 DC24V供电 输入：传感器重量信号 输出：4-20mA / 1-5V / RS-232 / RS-485应答或连续方式 DC 24V power supply Weighing transmitter Analog output: 4-20mA / 1-5V Serial output: RS-232 / RS-485 answering type or continuous type	采用标准插槽安装底座 Base of standard socket type
 **XK315A2-4** 塑料外壳 Plastic Housing	数据适配器 DC24V供电 输入：RS-232 / RS-485的连续信号 输出：4-20mA / 1-5V DC 24V power supply Data transmitter Input: RS-232 / RS-485 continuous signal Output: 4-20mA / 1-5V	采用标准插槽安装底座 Base of standard socket type
 **XK315A2-5** 塑料外壳 0.8英寸 红色LED显示 Plastic Housing 6-digit 20.2mm Red LED	输入：传感器重量信号 输出：4-20mA /1-5V / RS-232 / RS-485 连续方式 Input: weighing transmitter signal Output: 4-20mA / 1-5V / RS-232 / RS-485 continuous signal	台式安装 100-240V AC供电 Desktop installation method AC100-240V power supply
 **XK315A2-6** 塑料外壳 0.4英寸红色LED显示 Plastic Housing 6-digit 10mm Red LED	称重控制器 DC9V供电 XK315A2-6A型 4-20mA模拟电流输出 XK315A2-6B型 4-20mA模拟电流输出及6路继电器输出 2路带隔离的开关量输入 Weighing controller DC9V power supply XK315A2-6A is 4-20mA Analog output function XK315A2-6B is 4-20mA Analog output function and 6 relay outputs & 2 optical isolation input	嵌入式安装 可增配隔离型RS-232 / RS-485 Modbus-ASCII串行通讯 A型可选配AC交流供电 Embedded installation method Optional RS-232 / RS-485 Modbus-ASCII isolation interface Optional AC power on Model A
 **XK315A2-7** 6063铝外壳 0.8英寸高亮度红色LED显示 6063 Aluminum Housing 6-digit 20.2mm Red LED	称重控制器100-240V AC供电 标配RS-485带Modbus-RTU通讯协议 XK315A2-7A型 4-20mA模拟电流输出 / 0-10V模拟电压输出 XK315A2-7B型 4-20mA模拟电流输出 / 0-10V模拟电压输出及8路继电器输出、4路带隔离的开关量输入 Weighing controller AC100-240V power supply Standard RS-485 Modbus RTU communication XK315A2-7A is 4-20mA Analog output function XK315A2-7B is 4-20mA Analog output function and 8 relay outputs & 4 optical isolation input	嵌入式安装 可选配Profibus-DP总线集成接口 可选配Modbus-TCP网络通讯接口 可增配Profinet网络通讯接口 可增配独立RS-232或RS-485串行单向通讯 Embedded installation method Optional Profibus-DP communicate protocol Optional Modbus-TCP communicate protocol Optional Profinet communicate protocol Optional RS-232 / RS-485 isolation interface
 **XK315A2-9** 塑料外壳 0.8英寸高亮度红色LED显示 Plastic Housing 6-digit 10mm Red LED	重量变送器 DC24V供电 输入：传感器重量信号 输出：4-20mA 0-10 V / RS-485 Modbus RTU 应答方式或连续方式 / 2路开关量输入 Weighing transmitter DC24V Power supply Analog output: 4-20mA / 1-10V Serial output: RS-485 answering type or continuous type / 2 optical isolation input	导轨式安装 标配RS-485带Modbus-RTU通讯协议 Guide rail installation method Standard RS-485 Modbus -RTU communication

汽车衡仪表 / Truck Scales Weighing Indicators



XK315A6
塑料外壳
1.2英寸红色LED显示
Plastic Housing
6-digit 30.5mm Red LED



XK315A6P
塑料外壳自带微型打印机
1.2英寸红色LED显示
Plastic Housing built-in micro printer
6-digit 30.5mm Red LED

最多可接8只350Ω或16只700Ω传感器
更换仪表不用重新标定功能 / 四点线性修正 / 公斤-吨可选
最多可贮存10个单价、 200个车号、皮重和1000条称重记录
超载满量程的30%仪表将锁定 / 不间断实时时钟
日报表、月报表、分类（车号、货号）统计
中文填充式快速打印
两路独立RS-232串行连续输出通讯接口
24针针式打印输出
可增配RS-485串行口
可增配4G卡无线传输

Drive up to 8×350Ω or 16×700Ω load cell
Indicator can be replaced without recalibration
Four-point calibration / Selectable kg and t
Store and recall up to 10 unit prices and 200 vehicle numbers and tares and 1000 weighing records and statistical reports
Lock display when overload is greater 130%FS
Continuous real-time clock
Classify statistics by daily report, monthly report, vehicle and goods number
Filled print
Two RS-232 serial interfaces
Connect 24-pin dot matrix printer
Optional RS-485 serial interface
Optional 4G transmission



XK315A6GBP
0.8英寸绿色LED显示
304不锈钢外壳自带微型打印机
6-digit 20.2mm Green LED
304 stainless steel housing built-in micro printer



XK315A6GB
304不锈钢外壳
0.8英寸绿色LED显示
304 Stainless Steel Housing
6-digit 20.2mm Green LED

大屏幕 / Display



CX系列大屏幕
3英寸 / 5英寸 / 8英寸 共三款
CX series Remote Display
CX3S, CX5S, CX8S, totally 3 models



CX SS系列大屏幕
3英寸 / 5英寸 共两款
CX SS series 304 stainless steel housing remote display
CX3SS, CX5SS, totally 2 models



CX小精灵显示屏
CX1.2M单面或双面显示屏
外形尺寸：272×114×30mm
CX1.2M single-sided and double-sided display

可以连接60款以上知名称重仪器仪表，1200-9600之间波特滤自适应
Connect with more than 60 models famous weighing indicatos. Recognize baud rate of 1200-9600 automatically

防爆系列产品 / Explosion Proof Series Products



XK315A1EX-A/B
304不锈钢外壳
1英寸LCD显示
304 Stainless Steel Housing
6-digit 25.4mm LCD

最多可接4只350Ω或8只700Ω桥式传感器
kg-lb转换 / 动物秤功能 / 峰值保持功能 / 计数功能
HI / OK / LO 三区域定值显示
可增配RS-232 / RS-485 串行口
Drive up to 4×350Ω or 8×700Ω load cell
Selectable kg and lb / Animal weighing function
Peak hold function / Counting function
HI / OK / LO set-point
Optional RS-232 / RS-485 interface





防爆接线盒
304不锈钢外壳
4 / 6 / 8线 共3款
德国胡默尔防水PG接头
EX series Junction Box
304 Stainless Steel Housing
4 / 6 / 8 line, totally 3 models
Hummel PG connecters



防爆大屏幕
铝外壳
1.2英寸 / 3英寸 / 5英寸 共三款
EX series Remote Display
Aluminum Housing
EX-1.2M, EX-3M, EX-5M, totally 3 models



接线盒 / Junction Boxes

四线调桥压 / 信号接线盒
4 line junction boxes. Available in bridge adjustment or precision trim pot modes



GJ塑料接线盒
塑料外壳
外形尺寸：180×70×37mm
GJ series Junction box
Plastic housing



GI不锈钢接线盒
不锈钢外壳
外形尺寸：191×75×45mm
GI series Junction box
201 stainless steel housing



GC小精灵接线盒
不锈钢外壳
外形尺寸：192×96×38mm
美国伯恩斯电位器
GC series Junction box
304 stainless steel housing
Bourns potentiometers



XH小精灵接线盒
塑料外壳
外形尺寸：153×111×35mm
美国伯恩斯电位器
普通型和防水型可选
XH series Junction box
Plastic housing
Bourns potentiometers
Optional waterproof

4 / 6 / 8 / 10 / 12 线调桥压 / 信号接线盒
4 / 6 / 8 / 10 / 12 line junction boxes. Available in bridge adjustment or precision trim pot modes



GT系列塑料接线盒
ABS优质塑料外壳
外形尺寸：219×175×40mm
美国伯恩斯电位器
GT series Junction box
ABS housing
Bourns potentiometers



GA系列不锈钢接线盒
304不锈钢外壳 / 镜面材质上盖
外形尺寸：252×173×46mm
美国伯恩斯电位器
GA series Junction box
304 stainless steel housing
Mirror SS upper houing
Bourns potentiometers



YT系列塑料IP67防水接线盒
ABS优质塑料外壳 / 透明上盖
外形尺寸：219×175×40mm
美国伯恩斯电位器
YT series Waterproof Junction box
ABS housing
Transparent upper houing
Bourns potentiometers



YA系列不锈钢IP65防水接线盒
304不锈钢外壳 / 镜面材质上盖
外形尺寸：252×173×46mm
美国伯恩斯电位器
YA series waterproof Junction box
304 stainless steel housing
Mirror SS upper houing
Bourns potentiometers

配件 / Parts



XK315A1-DC1
1.2英寸高亮度红色LED显示
5-digit 30.5mm Red LED

吊秤板
A/D转换速度：10次/秒
综合精度：Ⅲ
置零范围：＜10%FS
去皮范围：10%FS-100%FS
无线遥控使用距离≤15米
Crane scale PCB
A/D conversion speed：10t/s
Overall precision：Ⅲ
Zero range：＜10%FS
Tare-removal range：10%FS-100%FS
Available distance of wireless control≤15m

可增配RS-232 / RS-485串行通讯
可增配蓝牙通讯接口
可增配无线大屏幕通讯接口
可增配消除由于晃动引起的称量误差功能
Optional RS-232 / RS-485 interface
Optional bluetooth communication
Optional to connect with remote display by wireless communication
Optional eliminate shaking weighing error function



CK针式打印机
EPSON原装机芯
使用寿命更久
打印更清晰
更换卷纸更便捷
Stylus Printer
EPSON mechanism
Longer service life
Clearer printing result
Easy to change the printing paper



201热敏打印机
58mm标签纸和热敏纸任意互换
有效打印最大范围宽48mm×高100mm
自动识别热敏连续纸或标签纸
修改标签格式更便捷
Thermal Printer
58mm thermal / label paper
Print effective range:48mm(W)×100mm(H)
Automatic recognition of thermal and label paper
Easy to set label format



蜂鸣报警灯
单色 / 双色 / 三色及蜂鸣报警
Warning lamp
All time light and blink is available
Red, yellow, green and beep warning

立杆座 / T-Holders



标配版
Standard T holder



多角度版
Multi angle T holder



高档304不锈钢版
304 stainless steel T holder

Quality and Peace of Mind

Wireless connection of indicator to load cell
Wireless connection of indicator to display



Dispaly



XK315A1RB-W



CRW2



LOAD CELL

无线传输

无线精彩

无限可能

上海彩信电子科技有限公司

SHANGHAI CAISUN ELECTRONIC TECHNOLOGY CO., LTD

地　　址：上海市浦东新区大团镇三墩三宣公路369弄25号
销售热线：021-58235785　58235786　58235788
传　　真：021-58235784
E-mail：caisun@caisun.com / shcx3@hotmail.com
网　　址：www.caisun.com

扫二维码 加微信公众号